
EXCEPT AS OTHERWISE PROVIDED BY CONTRACT, THIS DRAWING AND SPECIFICATIONS SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF MATTER DEPICTED HEREIN WITHOUT THE EXPRESSED WRITTEN PERMISSION OF THE LAKOS CORPORATION, OR ITS ASSIGNEES.


THIS DRAWING HAS BEEN GENERATED AND IS MAINTAINED BY A CAD SYSTEM. CHANGES SHALL ONLY BE INCORPORATED AS DIRECTED BY AN APPROVED ENGINEERING CHANGE ORDER (ECO).
PAPER COPIES ARE UNCONTROLLED.

REVISION HISTORY				
ECN / ECR	REV	DESCRIPTION	DATE	APPROVED
	C	UPDATED WITH INTERNAL VORTUBE	2/28/2025	MA
ECN-0101	D	REVIEW VORTUBE, UPDATE DRAWING VIEWS, UPDATE INLET MODEL	3/31/26	AMF


NOTES:

1. INLET & OUTLET FLANGES ARE 1/2" 150# RF PER ANSI B16.5 REQUIRING 4X ∅1/2" BOLTS (BOLTS AND GASKETS NOT INCLUDED).
2. MAXIMUM PRESSURE: 150 psi (10.3 bar).
3. MAXIMUM TEMPERATURE: 180°F (82.2°C).
4. PRESSURE LOSS: 3-12 psid (.2-.8 bar) AT RATED FLOW.
5. RATED FLOW: 4-10 gpm (1-2.5 m³/hr).
6. APPROXIMATE DRY WEIGHT: 31 lbs (14 kg).
7. FINISH: LAKOS BLUE (EXTERIOR ONLY).





TOP VIEW



FLANGED SPOOL
MODEL FS-0005 (AVAILABLE SEPARATELY)
REQUIRED FOR REMOVAL OF TOP ASSEMBLY

SUBMITTAL DRAWING

This drawing is submitted for spatial consideration only. Do not pre-plumb to these dimensions.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN: INCHES [mm] TOLERANCES ARE: FRACTIONS ± 1/2" DECIMALS .XX ± .01 .XXX ± .005 .XXXX ± .0005 ANGLES ± 1/4°	ENGINEERED FOR: FLANGED	LAKOS FILTRATION SOLUTIONS® FRESNO, CALIFORNIA WWW.LAKOS.COM	
DO NOT SCALE DRAWING	APPROVALS	DATE	TITLE: JPX-0004/FLG, SEPARATOR, 4-10 gpm, CARBON STEEL
MATERIAL: CLASS P-1 MILD CARBON STEEL	DRAWN DLW	4/3/06	
FINISH: LAKOS BLUE	ENGR DLW	4/3/06	SIZE C · MODEL NO. · DWG NO. 125874 · REV. D
	MFG -	-	SCALE 3:8 · EST. WT. 31 lb · SHEET 1 OF 1
	WORK ORDER	QTY.	

DWG NO. 125874 SH 1 REV D

GEDO
Distribution et conseil : GEDO FRANCE
04 85 88 02 75 | separateur@gedo.fr | separateurs.gedo.fr
565 avenue du Prado - 13008 Marseille - France