
EXCEPT AS OTHERWISE PROVIDED BY CONTRACT, THIS DRAWING AND SPECIFICATIONS SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF MATTER DEPICTED HEREIN WITHOUT THE EXPRESSED WRITTEN PERMISSION OF THE CLAUDE LAVAL CORPORATION, OR ITS ASSIGNEES.

THIS DRAWING HAS BEEN GENERATED AND IS MAINTAINED BY A CAD SYSTEM. CHANGES SHALL ONLY BE INCORPORATED AS DIRECTED BY AN APPROVED ENGINEERING CHANGE ORDER (ECO).
PAPER COPIES ARE UNCONTROLLED.


REVISION HISTORY				
ZONE	REV	DESCRIPTION	DATE	APPROVED

NOTES:


1. INLET & OUTLET ARE 1-1/4" GROOVED PIPE.
2. MAXIMUM PRESSURE: 150 psi (10.3 bar).
3. MAXIMUM TEMPERATURE: 180°F (82.2°C).
4. PRESSURE LOSS: 2-15 psid (.14-1.03 bar) AT RATED FLOW.
5. RATED FLOW: 25-60 gpm (3-7 m³/hr).
6. APPROXIMATE DRY WEIGHT: 115 lbs (52 kg).
7. FINISH: LAKOS BLACK (EXTERIOR ONLY).



TOP VIEW



BOTTOM VIEW



SUBMITTAL DRAWING

This drawing is submitted for spatial consideration only. Do not pre-plumb to these dimensions.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN: INCHES [mm]
TOLERANCES ARE:
FRACTIONS ± 1" | DECIMALS .XX ± .01, .XXX ± .005, .XXXX ± .0005 | ANGLES ± 1/4°
DO NOT SCALE DRAWING

MATERIAL: CLASS P-1 MILD CARBON STEEL

FINISH: LAKOS BLACK

ENGINEERED FOR: STANDARD

APPROVALS	DATE
DRAWN AMF	3/25/13
ENGR -	-
MFG -	-
WORK ORDER	QTY.

CLAUDE LAVAL CORP.
FRESNO, CALIFORNIA 93727
WWW.LAKOS.COM

LAVAL UNDERGROUND SURVEYS

TITLE: eHTX-0025-V, SEPARATOR, 25-60 gpm, CARBON STEEL

SIZE	MODEL NO.	DWG NO.	REV.
C		135773	01

SCALE 1:4 | EST. WT. 115 lb | SHEET 1 OF 1

DWG NO. 135773 SH REV. 01

GEDO
Distribution et conseil : GEDO FRANCE
04 85 88 02 75 | separateur@gedo.fr | separateurs.gedo.fr
565 avenue du Prado - 13008 Marseille - France