EXCEPT AS OTHERWISE PROVIDED BY CONTRACT, THIS DRAWING AND SPECIFICATIONS SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF MATTER DEPICTED HEREIN WITHOUT THE EXPRESSED WRITTEN PERMISSION OF THE LAKOS CORPORATION, OR ITS ASSIGNEES.


THIS DRAWING HAS BEEN GENERATED AND IS MAINTAINED BY A CAD SYSTEM. CHANGES SHALL ONLY BE INCORPORATED AS DIRECTED BY AN APPROVED ENGINEERING CHANGE ORDER (ECO).


PAPER COPIES ARE UNCONTROLLED.

REVISIONS				
ECN/ECR	REV.	DESCRIPTION	DATE	APPROVED
ECN-0101	I	INTERNAL VORTUBE UPDATE	3/6/2026	CG


NOTES:

1. INLET & OUTLET FLANGES ARE 6" 150# RF PER ANSI B16.5 REQUIRING 8X ∅3/4" BOLTS (BOLTS AND GASKETS NOT INCLUDED).
2. MAXIMUM PRESSURE: 150 psi (10.3 bar).
3. MAXIMUM TEMPERATURE: 180°F (82.2°C).
4. PRESSURE LOSS: 3-12 psid (.2-.8 bar) AT RATED FLOW.
5. RATED FLOW: 650-1200 gpm (150-275 m³/hr).
6. APPROXIMATE DRY WEIGHT: 1000 lbs (454 kg).
7. FINISH: LAKOS BLUE (EXTERIOR ONLY).







SECTION B-B



SECTION A-A





FLANGED SPOOL

MODEL FS-06 (AVAILABLE SEPARATELY)
REQUIRED FOR REMOVAL OF TOP ASSEMBLY

SUBMITTAL DRAWING

This drawing is submitted for spatial consideration only. Do not pre-plumb to these dimensions.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN: INCHES [mm] TOLERANCES ARE: FRACTIONS ± 1/4" DECIMALS .XX ± .01 .XXX ± .005 .XXXX ± .0005 ANGLES ± 1/4°	ENGINEERED FOR: FLANGED	LAKOS FILTRATION SOLUTIONS® FRESNO, CALIFORNIA WWW.LAKOS.COM
DO NOT SCALE DRAWING	APPROVALS / DRAWN CAG 11/29/07	TITLE: JPX-0650-L/FLG, SEPARATOR, 650-1200 GPM, CARBON STEEL
MATERIAL: CLASS P-1 MILD CARBON STEEL	ENGR JBI 11/29/07	
FINISH: LAKOS BLUE	MFG - -	SIZE C · MODEL NO. · DWG NO. 117592 · REV. I
	WORK ORDER · QTY.	SCALE 1:12 · EST. WT. 1002 lb · SHEET 1 OF 1

DWG NO. 117592 SH 1 REV. I

GEDO
Distribution et conseil : GEDO FRANCE
04 85 88 02 75 | separateur@gedo.fr | separateurs.gedo.fr
565 avenue du Prado - 13008 Marseille - France